

EXANE® CAT 5E

2 Pairs 22 AWG, NFPA 130 Compliant



90 °C • 100 Ohms • Low Smoke Zero Halogen • Train Car Applications
EIA/TIA 568-C.2 for CAT 5E • TD-008682

FEATURES

- Thermoset LSHF Insulation and Jacket
- Superior mechanical properties
- Ruggedized construction, excellent mechanical toughness
- Operating temperature -40 °C to 90 °C
- Passes temperature cycling test -30 °C to +125 °C, 250 cycles
- Ozone resistance
- Tested to the following RP-585 tests: Abrasion test, Notch Propagation, Crush, 26 weeks long term water, Cut through

PERFORMANCE STANDARDS

- EIA/TIA 568-C.2 for Category 5e cables
- Passes the spread of fire and smoke emissions test requirements for low voltage wire and cable in accordance with NFPA 130-2014 Article 8.6.7.1.1 for transit vehicle application. Passes UL 1685 flame test with IEEE 1202/FT4 Flame Method and smoke measurement.
- Passes the flame test requirement of 49 Code of Federal Regulations (CFR), Part 238 Appendix B, in accordance with NEMA WC3/ICEA S-19-81, paragraph 6.19.6.
- Passes the smoke test requirement of 49 Code of Federal Regulations (CFR), Part 238, Appendix B, in accordance with ASTM E662-97.
- Passes Toxicity Test requirements when tested in accordance with Boeing Specification Support Standard (BSS) 7239.
- ROHS and Reach compliant

CONSTRUCTION

Conductor: Stranded Tin Copper 22 AWG (7/30)

Insulation: Cross-Linked Low Smoke Halogen Free Insulation

Color Code: Pair #1: White/Orange Orange

Pair #2: White/Green Green

Pairs: Two Conductors twisted together with varying lay

Core Assembly: Two twisted pairs cabled together

Braid: 36 AWG, Tin Copper

Outer Jacket: Black, Cross-Linked Low Smoke Halogen Free Jacket

*Typical installation employs M12 connector, contact Electro Wire for more information.



EXANE CAT 5E TD-008682, 2 Pairs 22 AWG

Part Number	Number of Pairs	Conductor Stranding	Conductor Size MILS	Insulated Cond. Size MILS	Jacket Wall MILS	Overall Size IN	Weight LBS/ 1000 FT	Bend Radius IN
ED04022-003	2	7/30	30	62	35	0.315	53	3.15/6.3

Exane® is a registered trademark RSCC Wire & Cable LLC

CHICAGO
847.944.1500

BOSTON
978.534.5300

ATLANTA
678.297.1080

PHILADELPHIA
215.674.8773

DALLAS
469.467.0480

PHOENIX
623.478.8700

rtvsales@electrowire.com



www.electrowire.com

EXANE® CAT 5E

4 Pairs 24 AWG, NFPA 130 Compliant



90 °C • 100 Ohms • Low Smoke Zero Halogen • Train Car Applications
EIA/TIA 568-C.2 for CAT 5E • TD-009069

FEATURES

- Thermoset LSHF Insulation and Jacket
- Superior mechanical properties
- Ruggedized construction, excellent mechanical toughness
- Operating temperature -40 °C to 90 °C
- Passes temperature cycling test -30 °C to +125 °C, 250 cycles
- Ozone resistance
- Tested to the following RP-585 tests: Abrasion test, Notch Propagation, Crush, 26 weeks long term water, Cut through

PERFORMANCE STANDARDS

- EIA/TIA 568-C.2 for Category 5e cables
- Passes the spread of fire and smoke emissions test requirements for low voltage wire and cable in accordance with NFPA 130-2014 Article 8.6.7.1.1 for transit vehicle application. Passes UL 1685 flame test with IEEE 1202/FT4 Flame Method and smoke measurement.
- Passes the flame test requirement of 49 Code of Federal Regulations (CFR), Part 238 Appendix B, in accordance with NEMA WC3/ICEA S-19-81, paragraph 6.19.6.
- Passes the smoke test requirement of 49 Code of Federal Regulations (CFR), Part 238, Appendix B, in accordance with ASTM E662-97.
- Passes Toxicity Test requirements when tested in accordance with Boeing Specification Support Standard (BSS) 7239.
- ROHS and Reach compliant

SCOPE

Exane® CAT 5E TD-009069 is designed to operate on train cars, LRV, and people mover applications. It employs a rugged thermoset low smoke halogen free insulation and jacket compounds. The thermoset material provides superior resistance to abrasion, fire, and moisture. It may be installed in wet or dry locations. The cable complies with train cars specifications such as NFPA 130, ICEA S-19-81, ASTM E662, BSS 7239 and parts of RP-585.

CONSTRUCTION

Conductor: Stranded Tin Copper 24 AWG (7/32)

Insulation: Cross-Linked Low Smoke Halogen Free Insulation

Color Code: Pair #1: Brown/White Brown Pair #3: Green/White Green
Pair #2: Orange/White Orange Pair #4: Blue/White Blue

Pairs: Two Conductors twisted together with varying lay

Core Assembly: Four twisted pairs cabled together

Braid: 36 AWG, Tin Copper

Outer Jacket: Black, Cross-Linked Low Smoke Halogen Free Jacket

*Typical installation employs M12 connector, contact Electro Wire for more information.



EXANE CAT 5E TD-009069, 4 Pairs 24 AWG

Part Number	Number of Pairs	Conductor Stranding	Conductor Size MILS	Insulated Cond. Size MILS	Jacket Wall MILS	Overall Size IN	Weight LBS/1000 FT	Bend Radius IN
ED08024-008	4	7/32	24	49	35	0.342	54	3.5/5.25

Exane® is a registered trademark RSCC Wire & Cable LLC

CHICAGO 847.944.1500 **BOSTON** 978.534.5300 **ATLANTA** 678.297.1080 **PHILADELPHIA** 215.674.8773 **DALLAS** 469.467.0480 **PHOENIX** 623.478.8700

rtvsales@electrowire.com



www.electrowire.com